

Product Information*

Parking Place-Profile

- Combilift 552 | 552_MR | 542 | 542_MR | 543 | 543_MR
- Combiparker 560
- Parklift 405 | 450 | 340 | 401 | 411 | 421 | 403 | 413 | 461-463 | 464-465
- Parking Platform 501 | 503



* For new order delivery only

Product details



CLASSIC PROFILE

- Standard equipment
- Trapezoidal profile
- Galvanized (DIN EN ISO 1461 with 45 µm)
- Profile height 49 mm
- Raised profile for better drainage

- Corrosivity category C3
- Length of protection approx. 10–15 years
- Adjustable plastic brink wedges
- Rubber driving and walking mat available at extra charge



SMART PROFILE 2.0

- Optional equipment
- Flat profile
- Galvanized (DIN EN ISO 1461 with 45 µm)
- Profile height 49 mm*
- User-friendly due to excellent walkability and driveability
- Pleasing design
- Easy-care

- Corrosivity category C3
- Length of protection approx. 10-15 years
- Adjustable positioning aid



ALU PRIME PROFILE

- Optional equipment
- Extruded aluminium profile
- Anodized natural EV1
- Profile height 46 mm
- User-friendly due to excellent walkability and driveability
- Pleasing design
- Easy-care
- Lasting value cause extremely rust and weather-resistant**

- Corrosivity category C4
- Length of protection approx. 20 years
- Barrier-free
- Available for 2,0 to. + 2,6 to.
- Adjustable positioning aid
- Extended warranty on the ALU PRIME PROFILE with system maintenance contract

* 56 mm profile height at PARKING PLATFORMS 503

** With proper maintenance and cleaning

Accessories



Brink wedge

- For CLASSIC PROFILE
- Made of plastic
- Colour: Black
- Simple assembly
- Mobile
- Individually adjustable
- For comfortable parking



Positioning aid


- For SMART PROFILE 2.0 & ALU PRIME PROFILE
- Galvanized
- Individually configurable
- Comfortable to park



Rubber walking mat

- For CLASSIC PROFILE
- Made of rubber
- Colour: Black
- Simple assembly
- Individually insertable
- Comfortable to walk on
- With nubs for slip resistance

Please note:
Rubber moulded parts are subject to manufacturing tolerances. Distances of up to 20 mm can arise between the rubber mats.



Rubber driving mat

- For CLASSIC PROFILE
- Made of rubber
- Colour: Black
- Simple assembly
- Individually insertable
- Comfortable to drive on
- With nubs for slip resistance

Please note:
Rubber moulded parts are subject to manufacturing tolerances. Distances of up to 20 mm can arise between the rubber mats.

System compatibility

	CLASSIC PROFILE	SMART PROFILE 2.0	ALU PRIME PROFILE
Combilift 552 552_MR	●	○	○
Combilift 542 542_MR	●	○	○
Combilift 543 543_MR	●	○	○
Combiporter 560	○	●	○
Parklift 405 450	●	○	○
Parklift 340	●	○	○
Parklift 401 421	●	○	○
Parklift 411	●	-	-
Parklift 403 413	●	○	○
Parklift 461-463 464-465	●	○	○
Parking Platform 501	●	○	○
Parking Platform 503	-	●*	-

● Standard equipment, available for all parking systems

○ Optional equipment

* SMART PROFILE – profile height 56mm

- Not deliverable

We reserve the right to change design details, procedures and standards due to technical progress and environmental requirements.